

# Material Safety Data Sheet

## Butyl Cellosolve

22-06-2015



### 1. CHEMICAL PRODUCT and EMERGENCY TELEPHONE CONTACT

Product Name: Butyl Cellosolve

EMERGENCY TELEPHONE NUMBER: 0491-2566889

### 2. COMPOSITION/INFORMATION ON INGREDIENTS

Name	% by Weight
Butyl Cellosolve	99-100

### 3. HAZARDS IDENTIFICATION EMERGENCY OVERVIEW

**Potential Acute Health Effects:** Very hazardous in case of skin contact (irritant), of eye contact (irritant), of ingestion, of inhalation. Hazardous in case of skin contact (corrosive, permeator), of eye contact (corrosive). Liquid or spray mist may produce tissue damage particularly on mucous membranes of eyes, mouth and respiratory tract. Skin contact may produce burns. Inhalation of the spray mist may produce severe irritation of respiratory tract, characterized by coughing, choking, or shortness of breath. Inflammation of the eye is characterized by redness, watering, and itching. Skin inflammation is characterized by itching, scaling, reddening, or, occasionally, blistering.

**Potential Chronic Health Effects:** Hazardous in case of skin contact (irritant), of ingestion, of inhalation. **CARCINOGENIC EFFECTS:** Not available. **MUTAGENIC EFFECTS:** Mutagenic for mammalian somatic cells. Mutagenic for bacteria and/or yeast. **TERATOGENIC EFFECTS:** Not available. **DEVELOPMENTAL TOXICITY:** Not available. The substance may be toxic to kidneys, mucous membranes, skin, teeth. Repeated or prolonged exposure to the substance can produce target organs damage. Repeated p. 2 or prolonged contact with spray mist may produce chronic eye irritation and severe skin irritation. Repeated or prolonged exposure to spray mist may produce respiratory tract irritation leading to frequent attacks of bronchial infection.

#### POTENTIAL HEALTH EFFECTS

**Primary Routes of Entry:** Inhalation, skin contact/absorption, eye contact, and ingestion.

**General Acute Exposure:** Liquid, mist, or vapours can cause eye, skin, and respiratory tract irritation and Central Nervous System (CNS) depression.

**Inhalation:**

**Acute Exposure:** Short-term exposure to high concentrations may cause CNS depression. Symptoms may include headache, weakness, drowsiness, light-headedness, nausea, difficult breathing, drunkenness, eye irritation, blurred vision, blindness, loss of consciousness, vertigo, fatigue, convulsions, and possibly death, depending on exposure. Victims may improve and then get worse again up to 30 hours later.

**Skin:**

**Acute Contact:** Upon prolonged or repeated contact, absorption through the skin may occur and produce toxic effects similar to those resulting from inhalation exposure. Repeated or prolonged skin contact may cause drying, cracking, and inflammation of the skin due to the defatting action of the product.

**Eye:**

**Acute Contact:** Eye irritation may occur upon short-term exposure, including a burning sensation, tearing, redness, or swelling. Upon direct contact with liquid, conjunctivitis and corneal burns may occur. The primary toxic effect is exerted upon the nervous system, particularly the optic nerves and possibly the retina. The condition can progress to permanent blindness.

**Ingestion:** Ingestion may cause serious poisoning with effects similar to those of inhalation and absorption through the skin. Toxic effects are more common after ingestion. Death from as little as one ounce has been reported.

**Neurologic:**

**Acute Exposure:** Central Nervous System (CNS) depression may occur upon exposure.

**Summary of Chronic Exposure:** It is slowly eliminated from the body; hence repeated exposures may result in toxic levels in the blood and tissues. Due to its slow elimination, it should be regarded as a cumulative poison. Though single exposures to fumes may cause no harmful effect, daily exposure may result in the accumulation of sufficient amount in the body to cause illness.

**Note to the Physician:** Coma resulting from massive exposures may last as long as 2-4 days. In the body, products formed by its oxidation are formaldehyde and formic acid.

**Medical Conditions Aggravated by Exposure:** Personnel with pre-existing CNS disease, skin disorders, impaired liver or kidney function, GI tract disorders or chronic respiratory diseases should avoid exposure.

## 4. FIRST AID MEASURES

**First Aid for Eyes:** Immediately flush eyes with copious amounts of tepid water for at least 15 minutes. The patient should be seen in a health care facility and referral to an ophthalmologist considered.

**First Aid for Skin:** Immediately flush exposed area with copious amounts of tepid water for at least 15 minutes while removing contaminated clothing and shoes, followed by washing area thoroughly with soap and water. The patient should be seen in a health care facility if irritation or pain persists or if symptoms of toxicity develop. Wash contaminated clothing and shoes before reuse.

**First Aid for Inhalation:** Move patient to fresh air and keep warm and at rest. Monitor for respiratory distress. If difficulty in breathing develops or if breathing has stopped, administer artificial respiration and seek medical attention. If trained to do so administer supplemental oxygen with assisted ventilation as required. Caution: Administration of mouth-to-mouth resuscitation may expose the first aid provider to chemical within the victim's lungs or vomit.

**First Aid for Ingestion:** If patient is conscious, immediately give two glasses of water and induce vomiting. Do not make an unconscious person vomit. Get medical attention immediately.

## 5. FIRE FIGHTING MEASURES

**Extinguishing Media:** Water fog or fine spray. Dry chemical fire extinguishers. Carbon dioxide fire extinguishers. Foam. Alcohol resistant foams (ATC type) are preferred. General purpose synthetic foams (including AFFF) or protein foams may function, but will be less effective.

**Fire Fighting Procedures:** Keep people away. Isolate fire and deny unnecessary entry. Use water spray to cool fire exposed containers and fire affected zone until fire is out and danger of reignition has passed. Fight fire from protected location or safe distance. Consider the use of unmanned hose holders or monitor nozzles. Immediately withdraw all personnel from the area in case of rising sound from venting safety device or discoloration of the container. Burning liquids may be extinguished by dilution with water. Do not use direct water stream. May spread fire. Move container from fire area if this is possible without hazard. Burning liquids may be moved by flushing with water to protect personnel and minimize property damage.

**Special Protective Equipment for Firefighters:** Wear positive-pressure self-contained breathing apparatus (SCBA) and protective fire fighting clothing (includes fire fighting helmet, coat, trousers, boots, and gloves). Avoid contact with this material during fire fighting operations. If contact is likely, change to full chemical resistant fire fighting clothing with self-contained breathing apparatus. If this is not available, wear full chemical resistant clothing with self-contained breathing apparatus and fight fire from a remote location. For protective equipment in post-fire or non-fire clean-up situations, refer to the relevant sections.

**Unusual Fire and Explosion Hazards:** Container may rupture from gas generation in a fire situation. Violent steam generation or eruption may occur upon application of direct water stream to hot liquids.

**Hazardous Combustion Products:** During a fire, smoke may contain the original material in addition to combustion products of varying composition which may be toxic and/or irritating. Combustion products may include and are not limited to: Carbon monoxide. Carbon dioxide.

## **6. ACCIDENTAL RELEASE MEASURES**

**Spill or Leak Measures:** Stop leak if you can do it without risk. Keep unnecessary people away and deny entry. Isolate spill or leak area immediately for at least 330 to 660 feet in all directions. Stay upwind, out of low areas, and ventilate closed spaces before entering. Eliminate all ignition sources. Do not touch or walk through spilled material. Prevent entry of product into waterways, sewers, basements, or confined spaces. A vapour suppressing foam may be used to reduce vapours. All equipment used when handling the product must be grounded and/or spark resistant. Water spray may reduce vapours but may not prevent ignition in closed spaces. Fully encapsulating, vapour protective clothing should be worn for spills and leaks with no fire.

**Determining Spill Size:** Generally, a small spill is one that involves a single, small package (i.e. up to a 55 gallon drum), small cylinder, or a small (non-continuing) leak from a large container.

### **Large Spill:**

- a. Dike far ahead of liquid spill for later disposal.
- b. Follow local emergency protocol for handling.
- c. Water spray may reduce vapor; but may not prevent ignition in closed spaces.

### **Small Spill:**

- a. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal.
- b. Use clean non-sparking tools to collect absorbed material.

## **7. HANDLING AND STORAGE**

### **Handling General Handling:**

Avoid breathing vapor. Do not get in eyes, on skin, on clothing. Do not swallow. Keep container closed. Use with adequate ventilation. Wash thoroughly after handling. Keep away from heat, sparks and flame. See Section 8, EXPOSURE CONTROLS AND PERSONAL PROTECTION. Other Precautions: Containers, even those that have been emptied, can contain vapors. Do not cut, drill, grind, weld, or perform similar operations on or near empty containers. Spills of these organic materials on hot fibrous insulations may lead to lowering of the autoignition temperatures possibly resulting in spontaneous combustion.

## Storage

Store in the following material(s): Carbon steel. Stainless steel. Phenolic lined steel drums. Do not store in: Aluminum. Copper. Galvanized iron. Galvanized steel. See Section 10 for more specific information.

## 8. EXPOSURE CONTROLS, PERSONAL PROTECTION

**Skin Protection Requirements:** Equipment should prevent repeated or prolonged skin contact with the product. This may include rubber boots, resistant gloves, and other impervious and resistant clothing. Compatible materials may include butyl rubber, natural rubber, neoprene, nitrile rubber, viton and others. Review the equipment manufacture's compatibility data.

**Eye Protection Requirements:** Use chemical (indirectly vented) goggles when there is a potential for contact with product, including vapour. A full-face shield may be worn over goggles for additional protection, but not as a substitute for goggles.

**Other Protective Equipment:** Safety shower and eyewash fountain should be provided. Proper fire extinguishment equipment must be kept in the handling area.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point @ 760 mmHg, 1.01 ar	171 °C (340 °F)
Flash Point (Setaflash Closed Cup)	67 °C (153°F)
Freezing Point	-75 °C (-103°F)
Vapor pressure@ 20°C — extrapolated	0.66 mmHg, 0.117 kPa
Specific gravity (25/25°C)	0.901
Evaporation rate (n-butyl acetate = 1.0)	0.06
Solubility, g/L or % @ 25°C Solvent in water	100%

## 10. REACTIVITY

### Stability/Instability

Thermally stable at typical use temperatures.

**Conditions to Avoid:** Do not distill to dryness. Product can oxidize at elevated temperatures. Generation of gas during decomposition can cause pressure in closed systems.

**Incompatible Materials:** Avoid contact with: Strong acids. Strong oxidizers.

### Hazardous Polymerization

Will not occur.

### **Thermal Decomposition**

Decomposition products depend upon temperature, air supply and the presence of other materials. Decomposition products can include and are not limited to: Aldehydes. Ketones. Organic acids.

## **11. TOXICOLOGICAL INFORMATION**

### **Acute Toxicity**

#### **Ingestion**

LD50, Guinea pig 1,400 mg/kg LD50, Rat, male 1,746 mg/kg

#### **Skin Absorption**

LD50, Rat 2,270 mg/kg LD50, Guinea pig > 2,000 mg/kg

**Inhalation** LC50, 7 h, Vapor, Rat 700 ppm

#### **Sensitization**

**Skin** Did not cause allergic skin reactions when tested in humans. Did not cause allergic skin reactions when tested in guinea pigs.

### **Repeated Dose Toxicity**

In animals, effects have been reported on the following organs: blood (hemolysis) and secondary effects on the kidney and liver. Human red blood cells have been shown to be significantly less sensitive to hemolysis than those of rodents and rabbits.

### **Chronic Toxicity and Carcinogenicity**

In long-term animal studies with ethylene glycol butyl ether, small but statistically significant increases in tumors were observed in mice but not rats. The effects are not believed to be relevant to humans. If the material is handled in accordance with proper industrial handling procedures, exposures should not pose a carcinogenic risk to man.

## **12. ECOLOGICAL INFORMATION**

### **ENVIRONMENTAL FATE**

#### **Movement & Partitioning**

Bioconcentration potential is low (BCF less than 100 or log Pow less than 3). Potential for mobility in soil is high (Koc between 50 and 150). Henry's Law Constant (H): 1.60E-06 atm\*m3/mole Measured Partition coefficient, n-octanol/water (log Pow): 0.83 Measured Partition coefficient, soil organic carbon/water (Koc): 67 Estimated

### **Persistence and Degradability**

Material is readily biodegradable. Passes OECD test(s) for ready biodegradability. Material is ultimately biodegradable (reaches > 70% mineralization in OECD test(s) for inherent biodegradability).

## **13. DISPOSAL CONSIDERATIONS**

**Waste Disposal:** Waste must be disposed of in accordance with federal, state and local environmental control regulations

## **14. TRANSPORTATION INFORMATION**

Not classified as dangerous in the meaning of transport regulation.

## **15. REGULATORY INFORMATION**

### **California Proposition 65 (Safe Drinking Water and Toxic Enforcement Act of 1986)**

This product contains no listed substances known to the State of California to cause cancer, birth defects or other reproductive harm, at levels which would require a warning under the statute.

### **US. Toxic Substances Control Act**

All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements under 40 CFR 720.30

### **CEPA - Domestic Substances List (DSL)**

All substances contained in this product are listed on the Canadian Domestic Substances List (DSL) or are not required to be listed.

## **16. OTHER INFORMATION**

**Preparation Date :** 22-06-2015

**Prepared By :** Mereena Petrochemicals Pvt Ltd, NIDA, Kanjikkode, Palakkad, Kerala, India.

PIN: 678621

**Disclaimer:** The information above is believed to be accurate and represents the best information currently available to us. Users should make their own investigations to determine the suitability of

the information for their particular purposes. This document is intended as a guide to the appropriate precautionary handling of the material by a properly trained person using this product.